

## Surface care for glider transport trailers

Similar to gliders, airplane trailers are always painted white.

The good albedo of the white paint prevents the contents from heating up. To avoid damaging your valuable aircraft, trailers that are parked outdoors must be kept clean. Please do not use cleaning agents containing **strong solvents!**

Products from the automotive or boat sector are best suited for surface care. Please observe the respective processing instructions.

In general, care products should only be applied very thinly and polished out immediately after drying. Always apply to small areas. Never work in the sunshine! Most waxes react with UV rays when they are not hardened. This can lead to discoloration of the paintwork, especially if applied too thickly.

You should also not park your trailer under trees. The tannic acid from fallen leaves penetrates the paintwork and causes stains. This also applies in particular to birch seed, which stains strongly when combined with water. The dripping sap from drifting trees and bird droppings are also harmful. Acid rain often contains so much sulphur that it causes the streaks known in the car industry as 'environmental stains'. Only polishing out as quickly as possible will prevent permanent damage.

**A hard, well-polished layer of wax provides the best protection against all external stresses!**

**We recommend:**

Verschmutzungsgrad	Pflegeprodukt	Artikelnummer
gering, Grundreinigung	nextzett Auto-Glanzshampoo fluor	1672
gering	nextzett Express Polish	1675
mittel, mit Schmutz in Poren, leichte Kratzer	nextzett No 1 Clean & Polish <u>oder</u>	1674
	nextzett SF 1 Extreme Cut (neu)	1631
stark verschmutzt, verwittert	nextzett No 2 One Step Polish <u>oder</u>	1673
	nextzett SF 2 High Gloss Finish (neu)	1691
Nachbehandlung mit Wachs	nextzett Hartglanz <u>oder</u>	1632
	nextzett SF 3 Premium Protect (neu, silikonfrei)	1692

**“Nextzett (bisher 1Z)“ – Products have been tried and tested in aircraft and vehicle care for decades!**

Please note: All paint cleaners are abrasive. To avoid polishing through the paintwork at a later date, you should always use a product that is appropriate for the degree of soiling. It is harmful in the long term to treat light soiling with a strong cleaner.

- Repair damage immediately to prevent water ingress
- Do not apply solvents to the surface of the trailer
- Only apply a thin layer of care product and not in the sun
- Do not park under trees
- Polishing with paint cleaner
- Preserving with hard waxes